



Micropipetta Gilson Pipetman L P200L espulsore in acciaio

Micropipetta Pipetman Gilson P200 L, espulsore in acciaio inox



Product codes:

Reference: GL-2 FA10005M

Product gallery:



Product description:

Designed for performance and comfort, PIPETMAN® L comes in a comprehensive range of models, adapted to your needs in the lab. PIPETMAN L air-displacement pipettes cover a full volume range, including:

- Variable volume single channel models covering a volume range from 0.2 µL to 10 mL
- Variable volume multichannel models covering a volume range from 0.5 µL to 1200 µL, including four models equipped with V-rings (VR) at the bottom of the tip holders for a proper fit with most tip brands, covering a volume range from 20 µL to 300 µL

Comfortable, precise, accurate, and reliable, use PIPETMAN L pipettes confidently in your applications.



Convenient Use

Lightweight and balanced, PIPETMAN L combines an ergonomic design with minimized pipetting forces, giving you the ability to pipette longer without fatigue.

Right-handed or left-handed? No problem. Adjust the location of the tip ejector to the most comfortable position for you. PIPETMAN L single channel models are equipped with a stainless-steel tip ejector. Should your application require to pipette corrosive liquids, plastic tip ejectors are available as accessories. P5000L and P10mLL models are equipped with a plastic tip ejector to avoid direct contact with the tip and provide better compatibility with chemicals.

Secure Pipetting

Reduce pipetting errors and avoid accidental volume changes during pipetting cycles with a true volume-locking mechanism for improved accuracy and precision.

PIPETMAN L models are all fully autoclavable without disassembly for maximum convenience and protection from cross-contamination.

GLP Compliance

PIPETMAN L models feature a DataMatrix 2D code for easy traceability. Use a 2D code scanner to transfer the code automatically into any traceability or asset management system. Also, the pipette serial number is engraved on the body of the pipette for unique identification.

Specifications Adjustable or Fixed Volume Adjustable Volume Systematic error (µL) 20 µL = ± 0.50 µL

100 µL = ± 0.80 µL

200 µL = ± 1.60 µL Random error (µL) 20 µL = ± 0.20 µL

100 µL = ± 0.25 µL

200 µL = ± 0.30 µL Systemic Error (%) 10 % = ± 2.5 %

50 % = ± 0.8 %

100 % = ± 0.8 % Random Error (%CV) 10 % = ± 1.0 %

50 % = ± 0.25 %

100 % = ± 0.15 % Pipette Type Manual Air Displacement Volume Range 20-200 µL Pipette Model P200L Pipette Range PIPETMAN L Number of Channels 1 Ejector Type Metal Pack Size 1 Pack Size Unit Each



Shop name

Product features:

MPT - TYPE: mechanical variable
MPT - CHANNELS: 1
MPT - MAXIMUM CAPACITY: 200ul
MPT - RANGE: 20 - 200ul
MPT - DISPLAY: digital reading
MPT - EFFORT PIPETTING: -
MPT - BLOCK VOLUME: you
MPT - BUTTON: con codifica colore
MPT - EJECTION: mechanical
MPT - ID LABEL: no
MPT - CODING COLOR: you
MPT - RESISTANT TO UV: 108g
MPT - AUTOCLAVABLE: you
MPT - MAX TEMPERATURE: 121°C
MPT - MAIN FEATURES: -