Sistema ricircolo UV per inattivazione aria laboratorio con timer

Sistema ricircolo aria UV per purificazione aria di laboratorio programmabile

Product codes:

Reference: BS-040110-AAA

Product gallery:



Product description:

Il sistema di ricircolo aria UV mod. UVR-Mi è il nuovo modello potenziato.

Azione attiva su due fronti: radiazioni UV e azione catalitica di ossido di titanio sulle molecole biologiche di Virus, germi e altre molecole organiche tossiche;

Due modalità di operazione: breve periodo (sotto controllo del timer) - e modalità continua;

Indicazione delle ore di lavoro delle lampade UV;

è utilizzabile per inattivazione aria nei laboratori di ricerca, sale d'attesa, stazioni veterinarie ed ambulatoriali.

Lo strumento fornisce una protezione completa dalle radiazioni ultra-violette.

- - Fissabile al muro

- - Montabile su tripode con ruote

Product features:

CPP - TYPE: disinfettore air laboratory
CPP - FORM: compact
CPP - CAPACITY MAX: Productivity of the air flow 14 m3/h
CPP - DIMENSIONS: 110 x 135 x 660 mm
CPP - UV LAMP: 2x30W bactericidal
CPP - SUITABLE FOR PROTECTION FROM CONTAMINATION: V
CPP - PROTECTION MECHANISM: protection of the user from the UV light
CPP - OPTIONAL ACCESSORIES: tripod UVR-S
CPP - SPEED: 14 m3/h
CPP - FEATURES: model of greater power, with programmable timer
CPP - WEIGHT: 3.4 kg
CPP - POWER SUPPLY: 230 V, 50/60 Hz