




Agitatore basculante TubeRocker 24 rpm angolo 30°

Agitatore basculante TubeRocker velocità fissa 24 rpm angolo 30° - Capacità carico 2.3kg - Con piattaforma - Ideale per agitare provette e microtubi

**Product codes:**

Reference: 94 907 0001

Product gallery:**Product description:**

Agitatore TubeRocker basculante 2D a velocità fissa specifico per provette e microtubi
Compatibile con microtubi e provette da 1.5ml a 50ml
Mantiene in posizione le provette senza la necessita di ulteriori clamp o accessori

Product features:

STG - TYPE: agitator tilting
STG - CAPACITY: 30 x 1.5/2ml
STG - CAPACITY: 15 x 10ml
STG - CAPACITY: 15 x 15ml
STG - CAPACITY: 8 x 50ml
STG - FLOW: 2.3kg
STG - PLATFORM DIMENSIONS CM.: 30x11 ca
STG - MOVEMENT: tilting
STG - TILT: 30°
STG - RPM MAXIMUM: 24
STG - RPM MINIMUM: 24
STG - MODE OPERATIONS: command manual
STG - INTERFACE: analog
STG - DISPLAY: absent
STG - OPERATING CONDITIONS AMB.: da +4°C a 45°C
STG - FEATURES: agitatore base ideale per agitazione basculante delle provette
TSG - SIZE: 33.6x13.5x10cm



STG - WEIGHT: 1.8kg

STG - POWER: 230V - 50-60Hz - 50W

STG - ACCESSORIES INCLUDED: standard platform

STG - CAN BE USED WITH: microtubes 1.5 ml

STG - CAN BE USED WITH: test tubes 10ml

STG - CAN BE USED WITH: tubes 15ml type Falcon

STG - CAN BE USED WITH: tubes 50 ml type Falcon

STG - CAN BE USED WITH: provette fino a Ø30mm

STG - CAN BE USED WITH: microtubi 2.0